

**Durable,
Dependable,
and Accurate¹**



The New Face of Genius™ 3 Tympanic Thermometer Industry Standard Tested Performance, Improved Durability¹

Count on the Genius™ 3 Thermometer to deliver accurate readings¹

- Peak Select technology takes multiple readings and selects the highest temperature for display in 1 to 2 seconds.
- Rugged tip-based sensor construction improves durability, minimizing the need for recalibration.¹
- Disposable single-use probe covers help prevent cross-contamination.
- Programmable display shows oral, rectal, or an absolute temperature reading in ear mode.



PRODUCT SPECIFICATIONS

Accuracy

- +/- 0.3°C

Measurement Response Time

- 1–2 seconds

Ambient Operating Range

- +16°C–33°C (60.8°F–91.4°F)

Temperature Measurement Range

- +33°C–42°C (91.4°F–107.6°F)

Storage Temperature Range

- -25°C/+55°C

Battery Life

- 15,000 temperatures (3 AAA batteries)

Anti-Theft System

- Wall mount bracket/Genius™ mobile cart

Compliant with Standards

- ISO 80601-2-56:2017
- IEC 60601-1:2005/AMD1:2012
- IEC 60601-1-2:2014
- IEC 60601-1-11:2015 Ed.2

Warranty

- 3 year full manufacturer warranty

¹Internal data.

Genius™ 3 Thermometer: Robust, dependable and accurate¹

- Peak Select technology takes multiple readings and selects the highest temperature for display in 1 to 2 seconds.
- Rugged tip-based sensor construction improves durability, minimizing the need for recalibration.¹
- Disposable single-use probe covers help prevent cross-contamination.
- Programmable display shows oral, rectal, or an absolute temperature reading in ear mode.
- Redesigned plastic housing allows for an IP22 rating for protection against dust and liquid ingress.

Order Information

Code	Description	Ship Case
303013	Genius™ 3 Thermometer with Base	1
303030	Genius™ Probe Cover	2112
303058	Genius™ Locking Mount Wall	1